

## PRIME

**800 e kW 1000 kVA  
50 Hz 1500 rpm 400 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

Image shown may not reflect actual package.

## FEATURES

### FUEL/EMISSIONS STRATEGY

- Low Emissions

### DESIGN CRITERIA

- The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

### SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

### WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•S<sup>SM</sup> program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

### CAT® C32 ATAAC DIESEL ENGINE

- Utilizes ACERT™ Technology
- Reliable, rugged, durable design
- Four-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic engine control

### CAT GENERATOR

- Designed to match the performance and output characteristics of Cat diesel engines
- Single point access to accessory connections
- UL 1446 recognized Class H insulation

### CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

# PRIME 800 kW 1000 kVA

50 Hz 1500 rpm 400 Volts



## FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	• Air cleaner	
Cooling	• Package mounted radiator	
Exhaust	• Exhaust flange outlet	<input type="checkbox"/> Exhaust mufflers (except Tier 4)
Fuel	• Primary fuel filter with integral water separator • Secondary fuel filters • Fuel priming pump	
Generator	• Matched to the performance and output characteristics of Cat engines	<input type="checkbox"/> Oversize and premium generators <input type="checkbox"/> Permanent magnet excitation (PMG) <input type="checkbox"/> Internal excited (IE) <input type="checkbox"/> Anti-condensation space heaters
Power Termination	• Bus bar	<input type="checkbox"/> Circuit breakers, UL listed <input type="checkbox"/> Circuit breakers, IEC compliant
Control Panel	• EMCP 4 Genset Controller	<input type="checkbox"/> EMCP 4.2 <input type="checkbox"/> EMCP 4.3 <input type="checkbox"/> EMCP 4.4 <input type="checkbox"/> Generator temperature monitoring and protection <input type="checkbox"/> Load share module <input type="checkbox"/> Digital I/O module <input type="checkbox"/> Remote monitoring software
Mounting		<input type="checkbox"/> Rubber vibration isolators
Starting/Charging		<input type="checkbox"/> Battery chargers <input type="checkbox"/> Oversize batteries <input type="checkbox"/> Jacket water heater <input type="checkbox"/> Heavy duty starting system <input type="checkbox"/> Charging alternator <input type="checkbox"/> Air starting motor with control and silencer (3500 & C175 models only)
General	• Paint - Caterpillar Yellow except rails and radiators gloss black	The following options are based on regional and product configuration: <input type="checkbox"/> Seismic Certification per Applicable Building Codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, CBC 2007 <input type="checkbox"/> EU Certificate of Conformance (CE) <input type="checkbox"/> UL 2200 package <input type="checkbox"/> CSA Certification <input type="checkbox"/> EEC Declaration of Conformity <input type="checkbox"/> Enclosures- sound attenuated, weather protective <input type="checkbox"/> Automatic transfer switches (ATS) <input type="checkbox"/> Integral & sub-base fuel tanks <input type="checkbox"/> Integral & sub-base UL listed dual wall fuel tanks

# PRIME 800 kW 1000 kVA

50 Hz 1500 rpm 400 Volts



## SPECIFICATIONS

### CAT GENERATOR

Frame size..... 1402  
Excitation..... Internal Excitation  
Pitch..... 0.6667  
Number of poles..... 4  
Number of bearings.....1  
Number of Leads..... 006  
Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion  
- Consult your Caterpillar dealer for available voltages  
IP Rating..... IP23  
Alignment..... Closed Coupled  
Overspeed capability..... 150  
Wave form Deviation (Line to Line)..... 002.00  
Voltage regulator..... 3 Phase sensing with selectable volts/Hz  
Voltage regulation..... Less than +/- 1/2% (steady state)  
Less than +/- 1% (no load to full load)

### CAT DIESEL ENGINE

C32 TA, V-12, 4-Stroke Water-cooled Diesel  
Bore..... 145.00 mm (5.71 in)  
Stroke..... 162.00 mm (6.38 in)  
Displacement..... 32.10 L (1958.86 in<sup>3</sup>)  
Compression Ratio..... 15.0:1  
Aspiration..... TA  
Fuel System..... MEUI  
Governor Type..... ADEM™ A4

### CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- kW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse reactive power (kVA) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

# PRIME 800 ekW 1000 kVA

50 Hz 1500 rpm 400 Volts



## TECHNICAL DATA

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM9946	
<b>Low Emissions</b>		
<b>Generator Set Package Performance</b> Genset Power rating @ 0.8 pf Genset Power rating with fan	1000 kVA 800 ekW	
<b>Fuel Consumption</b> 100% load with fan 75% load with fan 50% load with fan	224.2 L/hr 168.1 L/hr 115.2 L/hr	59.2 Gal/hr 44.4 Gal/hr 30.4 Gal/hr
<b>Cooling System<sup>1</sup></b> Air flow restriction (system) Engine coolant capacity	0.12 kPa 55.0 L	0.48 in. water 14.5 gal
<b>Inlet Air</b> Combustion air inlet flow rate	72.0 m <sup>3</sup> /min	2542.7 cfm
<b>Exhaust System</b> Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	501.1 °C 193.7 m <sup>3</sup> /min 203 mm 10.0 kPa	934.0 °F 6840.5 cfm 8 in 40.2 in. water
<b>Heat Rejection</b> Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	288 kW 881 kW 223 kW 107 kW 50.2 kW	16379 Btu/min 50102 Btu/min 12682 Btu/min 6085 Btu/min 2854.9 Btu/min
<b>Alternator<sup>2</sup></b> Motor starting capability @ 30% voltage dip Frame Temperature Rise	2297 skVA 1402 125 °C	225 °F
<b>Lube System</b> Sump refill with filter	99.0 L	26.2 gal
<b>Emissions (Nominal)<sup>3</sup></b> NOx mg/nm <sup>3</sup> CO mg/nm <sup>3</sup> HC mg/nm <sup>3</sup> PM mg/nm <sup>3</sup>	1850.7 mg/nm <sup>3</sup> 77.2 mg/nm <sup>3</sup> 15.1 mg/nm <sup>3</sup> 9.8 mg/nm <sup>3</sup>	

<sup>1</sup> For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

<sup>2</sup> UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40°C ambient per NEMA MG1-32.

<sup>3</sup> Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

# PRIME 800 ekW 1000 kVA

50 Hz 1500 rpm 400 Volts



## RATING DEFINITIONS AND CONDITIONS

---

**Applicable Codes and Standards:** AS1359, CSA C22.2 No 100-04, UL142, UL489, UL601, UL869, UL2200, NFPA 37, NFPA 70, NFPA 99, NFPA 110, IBC, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, 72/23/EEC, 98/37/EC, 2004/108/EC

**Continuous** - Output available with non-varying load for an unlimited time. Average power output is 70-100% of the continuous power rating. Typical peak demand is 100% of continuous rated ekW for 100% of operating hours.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions.

**Fuel Rates** are based on fuel oil of 35° API (16° C or 60° F) gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.).

**Additional Ratings** may be available for specific customer requirements. Consult your Cat representative for details.

# PRIME 800 kW 1000 kVA

50 Hz 1500 rpm 400 Volts



## DIMENSIONS

---

Package Dimensions		
Length	4234 mm	116.7 in
Width	2010 mm	79.2 in
Height	2174 mm	85.6 in

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing 434-5852).

Performance No.: DM9946

Feature Code: C32DR37

Gen. Arr. Number: 432-6118

Source: U.S. Sourced

EPD0166-A (06/13)

[www.Cat-ElectricPower.com](http://www.Cat-ElectricPower.com)

2013 Caterpillar  
All rights reserved.

Materials and specifications are subject to change without notice.  
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.