

Specifications for Model 2630ES

DIMENSIONAL DATA

Platform Height- Elevated	25 ft 6 in. (7.77 m)
Platform Height - Lowered	48.5 in. (1.23 m)
Platform Railing Height	43.3 in. (1.10)
- With Rails Folded	6 ft 4.5 in. (1.94 m)
Platform Size	30 x 90.5 in. (0.76 x 2.3 m)
Platform Extension	35.5 in. (90 cm)
Overall Height	7 ft 7.8 in. (2.33 m)
Overall Width	30 in. (76 cm)
Overall Length	7 ft 6.5 in. (2.3 m)
Wheelbase	6 ft 2 in. (1.88 m)
Ground Clearance	3.5 in. (89 mm)
Platform Capacity	500/800 lb (227/363 kg)
Capacity on Platform Extension	250 lb (113 kg)
Lift/Lower Time	40/40 sec.
Maximum Drive Height	Full Height
Weight*	4,750 lb (2,155 kg)

* certain options or country standards will increase weight

PERFORMANCE DATA

Drive Speed - Lowered	2.75 mph (4.43 kmph)
Drive Speed - Elevated	0.5 mph (0.8 kmph)
Gradeability	25%
Turning Radius (Inside)	0
Turning Radius (Outside)	81 in. (2.06 m)
Tire Size, (Non-Marking Solid)	16 x 5 in. (406 x 125 mm)
Brakes (On Drive Wheels)	Electric, Friction

POWER SOURCE/CHASSIS

Batteries	4 x 6V 220 amp-hr
Charger	20 Amp Automatic
Pump	Fixed Clearance Gear
Hydraulic Reservoir	1.25 gal. (4.73 L)
Rail Type	Fold Down
Drive	24V Electric (8 hp)