



# FB 260

## Reversible vibratory plate

### For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The Swepac FB 260 is a high-performance diesel powered, reversible compactor with electric start.
- The compact design makes it suitable in trenches and other areas with limited space. With a Vulkollan® plate (accessory) attached to the base, it can compact paved areas efficiently for an even surface.
- The Hardox® wear plate in the base ensures a long service life.
- The chassis is hot-dip galvanized, which means superior corrosion protection, and the sturdy protective frame, with a collapsible lifting eye that is easily accessible, provides effective protection against external damage.
- The machine is equipped with infinitely variable speed control, for easy operation.
- The machine is designed to be highly ergonomic and includes an effective low vibration handlebar with a heating element.

Swepac is Sweden's leading manufacturer of soil compactors. The company has a wide range of products, with different motor options and a variety of sizes for every application. Swepac is certified for quality and environmental management under ISO 9001 and 14001, and our machines are Eurotest-certified by SMP Swedish Machinery Testing Institute. You will find detailed information about the company and our products on our website, [www.swepac.com](http://www.swepac.com). We reserve the right to make changes in technical specifications without prior notice.

Swepac AB  
Blockvägen 3 | SE-342 32 Ljungby | Sweden  
Tel +46 (0)372-156 00 | [www.swepac.com](http://www.swepac.com)

#### TECHNICAL DATA SWEPAC FB 260

Net, weight	265 kg
Base plate, width	550 mm
Height, max / min	1200 / 1030 mm
Length, max / min	1530 / 900 mm
Engine	Hatz 1B 30
Fuel tank capacity	3.5 liter
Fuel	Diesel
Engine output, max	4.8 kW
Centrifugal force	40 kN
Working speed	0 - 25 m/min
Hand/arm vibrations $a_{hv}$ according to ISO 5349 on gravel surface	2.7 m/s <sup>2</sup>
Guaranteed sound-power level, $L_{WA}$	108 dB(A)
Sound pressure level (at operators ear)	95 dB(A)

#### Part number

303197	FB 260 with Hatz diesel engine
--------	--------------------------------

#### Accessories

303139	Vulkollan plate complete
--------	--------------------------

FB260\_2013-03\_GB

**swepac**